

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 950 376 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
20.10.1999 Bulletin 1999/42

(51) Int. Cl.⁶: A61B 17/34

(21) Application number: 98308090.4

(22) Date of filing: 05.10.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Shimomura, Kazuyuki
Nerima-ku, Tokyo (JP)
• Tamai, Yukihiro,
c/o Hakko Elect.Mach.Wks,Co,Ltd
Nagano-ken (JP)

(30) Priority: 07.04.1998 JP 9507798

(71) Applicants:
• Hakko Electric Machine Works, Co., Ltd.
Hanishina-gun, Nagano-ken (JP)
• Shimomura, Kazuyuki
Tokyo (JP)


(74) Representative:
Jackson, Peter Arthur
GILL JENNINGS & EVERY
Broadgate House
7 Eldon Street
London EC2M 7LH (GB)

(54) Valved surgical access port

(57) Disclosed is a valved trocar jacket tube, in which both ends of a first cylindrical elastic member are secured, one end of a second cylindrical elastic member is attached to one of first and second rings, which are so constructed that when they are rotated relatively in the opposite directions the opening of the first cylindrical elastic member is closed from the opening state, and a fluid container is provided at a predetermined

position of the second cylindrical elastic member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid. According to this structure, it is possible to provide a valved trocar jacket tube, which can prevent leakage of an inert gas from an abdominal cavity without reducing the operativity during surgery.

FIG.5



EP 0 950 376 A1

Description

[0001] The invention relates to a valved trocar jacket tube which is used in endoscopic surgery in pneumoperitoneum, and more particularly to a trocar jacket valve, which can prevent leakage of an inert gas from an abdominal cavity without decreasing operativity during the surgery.

[0002] Fig. 1 shows a first conventional valved trocar jacket tube, wherein the conventional trocar jacket tube 1 comprises a cylindrical jacket 2 and a casing 3 secured to the top of the jacket 2. The casing 3 is provided with a circular opening 3a on the upper part thereof. Furthermore, the casing 3 contains a valve 4 for opening and closing the opening 3a on the inside thereof and a spring 5 for urging the valve 4 in the closing direction therein.

[0003] When the valved trocar jacket tube 1 thus constituted is employed, as shown in Fig. 2, the surgeon inserts the jacket 2 of the valved trocar jacket tube 1 into a site, for example, an abdominal incision Pa of a patient P being an object to be operated. In case of using a clamp (forceps) or the like 7, an adapter 6 called as reducer or introducer is used, which comprises a leakage preventing valve 6A having a opening 6a an inner diameter of which corresponds to an outer diameter of the clamp or the like 7 and a outer cylinder 6B. The surgeon gets the clamp or the like 7 having a diameter corresponding to the opening 6a of the adapter 6 thereto, and the adapter 6 is inserted through the opening 3a of the casing 3. In this case, the valve 4 is opened against the spring force of the spring 5 due to insertion of the adapter 6. As a result, leakage of an inert gas injected into an abdominal cavity for conducting easily endoscopy or the like is prevented.

[0004] According to the first conventional valved trocar jacket tube 1, however, there is a disadvantage in that since the diameter of the opening 3a provided on the casing 3 is constant, it is required to use an adapter 6 having the diameter corresponding to that of the clamp or the like 7 to be used, and the substitution to another adapter is troublesome, thereby preventing the operator's manipulation.

[0005] Further, there is another disadvantage in that since the standard sizes of the opening 6a of the adapter 6 are usually 5mm, 10mm, and 12mm, a clamp or the like having an intermediate size such as 6mm or 8mm cannot be used, so that the sizes of the clamp or the like 7 are also restricted.

[0006] Still further, since the inner diameters of the openings 6a of the adapter 6 and the outer diameters of the clamp or the like 7 are nominal values, respectively, there is the other disadvantage in that the inner diameter of the opening 6a of the adapter 6 may not match with the outer diameter of the clamp or the like 7. As a result, it is impossible to use the clamp or the like 7 or it may cause leakage of the inert gas.

[0007] For solving these problems, the Applicant pro-

posed a valved trocar jacket tube of another type in Japanese Patent Application No. 8-266883 (Japanese Patent Application Laid-Open No.10-108868) filed on October 8, 1996, wherein the valved trocar jacket tube comprises a first cylindrical elastic member having an opening with a predetermined sectional area, a pair of rings, to which the ends of the first cylindrical elastic member are attached respectively, and which are so constructed that when they are rotated relatively in the opposite directions the opening of the first cylindrical elastic member is closed from the opening state, a second cylindrical elastic member to be inserted into an abdominal incision, one end of which is attached to one of the pair of rings, and a ring shaped elastic member provided at another end of the second cylindrical elastic member, which enlarges another end of the second cylindrical elastic member and contacts it closely to the abdominal incision.

[0008] According to the second conventional valved trocar jacket tube, when a pair of rings are rotated relatively in the opposite directions, an opening of a first cylindrical elastic member is closed due to the twist of the first cylindrical elastic member, so that it will fit securely and flexibly with the hands of the surgeon or the clamp or the like, which is preliminarily inserted into a incised portion of a diseased part through the opening. As a result, the types of clamps or the like to be employed are not limited and it is possible to use the clamps of the intermediate sizes or the clamps having contours other than a circular shape. Further, since the use of an adapter becomes unnecessary, it is not necessary to conduct substituting operation of the adapter, so that endoscopic surgery can be conducted smoothly. Still further, since the second cylindrical elastic member fits securely with an abdominal incision due to the tension thereof, the airtightness of an abdominal cavity can be kept and leakage of an inert gas from the abdominal cavity can be prevented.

[0009] On the other hand, U.S Patent No. 5,366,478 discloses a valved trocar jacket tube of the other type. This third conventional valved trocar jacket tube contains a pair of ring-shaped elastic members on the inside thereof and comprises a cylindrical air container having an opening provided at the central portion thereof, in which the opening section is changed to have a predetermined sectional area from the closed state due to injection of an air. This valved trocar jacket tube is such constructed that one of the pair of the ring-shaped elastic members is inserted into an abdominal cavity through an abdominal incision and air is injected into the cylindrical air container, so that the cylindrical air container fits securely to the abdominal incision.

[0010] According to the second conventional valved trocar jacket tube proposed by the Applicant, however, since the contacting force is determined in accordance with an outer diameter of the second cylindrical elastic member and the contour of the abdominal incision, when the contour of the abdominal incision becomes

relatively large, the contact between the second cylindrical elastic member and the abdominal incision becomes insufficient, so that an inert gas is leaked from a gap defined by the second cylindrical elastic member and the abdominal incision.

[0011] On the other hand, according to the third conventional valved trocar jacket tube disclosed in U.S. Patent No. 5,366,478, when the hand of the surgeon or the clamps or the like is inserted into an abdominal cavity or it is pulled out therefrom, it is necessary to adjust the volume of an air injected into an air container. It is troublesome to conduct such an adjustment of the air volume for several times during the surgery, and it is impossible to avoid the leakage of an inert gas from the abdominal cavity at this time. Further, in view of decreasing the leakage of the inert gas to the minimum, if the air volume of the cylindrical air container is not reduced so much, the inserted hand or clamp or the like may scratch the cylindrical air container, and when the things come to the worst, it may be damaged.

[0012] Accordingly, it is an object of the invention to provide a valved trocar jacket tube, which can prevent leakage of an inert gas from an abdominal cavity without decreasing operativity during the surgery.

[0013] According to the first feature of the invention, a valved trocar jacket tube, comprises:

a first cylindrical elastic member having an opening with a predetermined sectional area;

closing means including a first ring for securing one end of the first cylindrical elastic member and a second ring for securing another end of the first cylindrical elastic member, the first and second rings rotating relatively in the opposite directions respectively for closing the opening from an opened state;

a second cylindrical elastic member, one end of which being attached to one of the first and second rings;

a ring member, which is elastically deformable and provided at another end of the second cylindrical elastic member; and

a fluid container provided at an upper part of an outer side of the second cylindrical elastic member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid;

wherein:

the first cylindrical elastic member is positioned outside an incised portion of a diseased part and functions as a valve;

the second cylindrical elastic member is positioned from outside to inside of the incised portion of the diseased part and maintains the incised portion at an opened state;

the ring member is positioned inside of the incised portion of the diseased part and engaged with the incised portion of the diseased part; and

the fluid container is positioned outside the incised portion of the diseased part and fits securely the second cylindrical elastic member to side walls of the incised portion of the diseased part.

[0014] It is preferable that the fluid container is provided on the upper part of the outer side of the second cylindrical elastic member and detachable therefrom.

[0015] It is preferable that the closing means is connected to another closing means for closing on opening of a third cylindrical elastic member from an opened state.

[0016] According to the second feature of the invention, a valved trocar jacket tube, comprises:

a first cylindrical elastic member having an opening with a predetermined sectional area;

closing means including a first ring for securing one end of the first cylindrical elastic member and a second ring for securing another end of the first cylindrical elastic member, the first and second rings rotating relatively in the opposite directions respectively for closing the opening from an opened state;

a second cylindrical elastic member, one end of which being attached to one of the first and second rings; and

a fluid container provided at an upper part of an outer side of the second cylindrical elastic member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid;

wherein:

the first cylindrical elastic member is positioned outside an incised portion of a diseased part and functions as a valve;

the second cylindrical elastic member is positioned from outside to inside of the incised portion of the diseased part and maintains the incised portion at an opened state; and

the fluid container is positioned inside the incised portion of the diseased part and fits securely the second cylindrical elastic member to side walls of the incised portion of the diseased part.

[0017] It is preferable that the fluid container is bonded or fused to the another end of the second cylindrical elastic member.

[0018] It is preferable that the fluid container is constructed by piling a lower end of the second cylindrical elastic member to have a tube shape and bonding or fusing it to a predetermined portion of the second cylindrical elastic member.

[0019] It is preferable that the closing means is connected to another closing means for closing an opening of a third cylindrical elastic member from an opened state.

[0020] The invention will be explained in more detail in

conjunction with appended drawings, wherein:

Fig. 1 is a cross-sectional view showing a conventional valved trocar jacket tube;

Fig. 2 is a cross-sectional view showing a conventional valved trocar jacket tube as employed;

Figs. 3A and 3B show a valved trocar jacket tube in a first preferred embodiment according to the invention, wherein Fig. 3A is a plan view thereof and Fig. 3B is a cross-sectional view thereof;

Figs. 4A and 4B show the opened state of a valved trocar jacket tube in the first preferred embodiment according to the invention, wherein Fig. 4A is a plan view thereof and Fig. 4B is a cross sectional view thereof;

Fig. 5 is a cross-sectional view showing a valved trocar jacket tube as employed in the first preferred embodiment according to the invention;

Fig. 6 is a cross-sectional view showing a valved trocar jacket tube in a second preferred embodiment according to the invention;

Fig. 7 is a cross-sectional view showing a valved trocar jacket tube in a third preferred embodiment according to the invention;

Figs. 8A and 8B show a valved trocar jacket tube in a fourth preferred embodiment according to the invention, wherein Fig. 8A is a cross-sectional view thereof and Fig. 8B is a cross-sectional view thereof as employed; and

Fig. 9 is an explanatory diagram showing a variation of an air container in the fourth preferred embodiment according to the invention.

[0021] Next, a valved trocar jacket tube in the preferred embodiments according to the invention will be explained in detail as set out below.

[0022] Figs. 3A and 3B show a valved trocar jacket tube in a first preferred embodiment according to the invention, wherein a valved trocar jacket tube 100A comprises a valve 10 and a skirt 110 functioning as jacket means, and the skirt 110 is attached to the valve 10.

[0023] The valve 10 is composed of a pair of a male ring 11 and a female ring 12 placed oppositely to each other and a cylindrical rubber-like member 13 functioning as an elastic member the ends of which are attached to the pair of the rings 11 and 12, respectively.

[0024] The pair of rings 11 and 12 are prepared from a corrosion-resistant material such as metals, for example, stainless steel (SUS 304, 316, etc.), titanium, titanium alloys, aluminum, and aluminum alloys; ceramics; and high polymeric organic materials. Grooves 11a and 12a into which is fitted an end portion 13b of the rubber-like member 13 which will be explained hereafter are defined on the outer circumference of the pair of the rings 11 and 12, respectively. Furthermore, on the sides of the opposed pair of the rings 11 and 12 are defined step portions 11b and 12b being slid with each other.

The pair of the rings 11 and 12 are arranged in such that they are rotatable relatively in the opposite directions due to the guiding action of the step portions 11b and 12b. Moreover, engage-grooves 11A and 12A are provided with faces contacting to each other of the pair of the rings 11 and 12, respectively, so that the rotation of the female ring 12 in the counter-clockwise direction is restricted by engaging force. The outer diameter of the pair of the rings 11 and 12 may be selected in response to the outer diameter of a member to be inserted into the valve 10. For example, it is preferred that the outer diameter thereof is around 100 mm in case of inserting an operator's hand into the valve, and it is around 30 mm in case of insertion of only a clamp (forceps) or the like. Moreover, the pair of rings 11 and 12 may be formed into somewhat elliptical shape, so that when either of the rings 11 or 12 is rotated at a predetermined angle in either direction, they are adapted to be braked.

[0025] The rubber-like member 13 is constituted in such that a cylindrical section 13a of the rubber-like member 13 is closed or opened when the pair of the rings 11 and 12 are relatively rotated in the opposite directions. More specifically, the rubber-like member 13 is formed from a thin film having a thickness of around 30 to 50 μ m and made from a material having elasticity such as caoutchouc (natural rubber), synthetic rubber, polyvinyl chloride, silicone rubber, and a variety of elastomers. The rubber-like member 13 includes an opening 13c having a predetermined cross-sectional area at the central portion thereof, and is shaped in such that the diameter of which decreases in the direction from the opposite ends to the central opening 13c of the rubber-like member 13 (see Fig. 2). Furthermore, convex portions 13b which are fitted in the grooves 11a and 12a of the pair of the rings 11 and 12 are formed on the opposed ends of the rubber-like member 13, so that the rubber-like member 13 is detachable from the grooves 11a and 12a. Because of such detachable structure of the rubber-like member 13, it can be easily replaced by another rubber-like member 13 in the case when the used rubber-like member 13 is broken, etc.

[0026] Figs. 4A and 4B show an opened state of a cylindrical section 13d of the valve 10 for inserting a member to be inserted. When the female ring 12 is slightly rotated in the clockwise direction from the closed state of the cylindrical section 13a of the rubberlike member 13, so that the engaged state between the engage-groove 11A of the male ring 11 and the engage-groove 12A of the female ring 12 is released. Due to the resilient force of the rubber-like member 13, the female ring 12 is rotated at 180° in the counter clockwise direction, so that the cylindrical section 13a is opened and the pair of the rings 11 and 12 are separated from each other simultaneously, as shown in Fig. 4B. Further, when the female ring 12 is rotated at 180° in the clockwise direction against its resilient force, the pair of the rings 11 and 12 are joined with each other and the cylindrical section 13a is twisted to become a closed state as shown in

Figs. 4A and 4B. Next, while the step portion 11b of the male ring 11 and the step portion 12b of the female ring 12 are contacted with each other, the rotating force of the female ring 12 in the clockwise direction is released, so that the female ring 12 is rotated in the counter clockwise direction due to the resilient force of the rubber-like member 13. Then, the engage-groove 11A of the male ring 11 and the engage-groove 12A of the female ring 12 are engaged with each other, so that the state shown in Figs. 4A and 4B is maintained.

[0027] The skirt 110 is composed of a cylindrical member 111 made of rubber or the like having the thickness of around 100 μm and a contour the diameter of which decreases from both the upper and lower ends towards a predetermined portion thereof, a ring-shaped air container 112 made of elastic material such as silicone rubber, etc., which is attached to the lower end of the cylindrical member 111 by bonding or fusion, and an air injecting inlet 113 which is provided with the air container 112 for injecting an air thereto and functions as a back-flow preventing valve for preventing the back-flow, of the injected air. The upper end of the cylindrical member 111 is bonded or fused in vicinity of the convex portion 13b which is fitted into the groove 11b of the male ring 11 of the rubber-like member 13. Alternately, the upper end of the cylindrical member 111 may have such a constitution that it is fitted into the groove 11a of the male ring 11. By this structure, when the skirt 110 is broken, etc., it can be easily replaced by another new skirt 110.

[0028] Fig. 5 shows a valved trocar jacket tube 100A as used in the first preferred embodiment according to the invention, wherein P_1 is a skin of a patient P, P_2 is an abdominal wall of the patient P, and P_3 is a peritoneum of the patient P. For mounting the valved trocar jacket tube 100A, an air is injected into the air container 112 through the air injecting inlet 113 such that the air container 112 is inflated to have a desired outer diameter corresponding to the contour of an abdominal incision Pa. At this stage, the under side of the skirt 110 is inserted into the abdominal incision of the patient P while forcing the air container 112 to have a slender elliptical shape. Thereafter, the air container 112 is inflated into the circular configuration in an abdominal cavity to engage with the abdominal incision Pa as shown in Fig. 5. At this time, the cylindrical member 111 and an upper side of the air container 112 fit securely with a portion of the peritoneum P_3 of the abdominal incision Pa and the other portion of the peritoneum P_3 placed in the abdominal cavity, respectively. Then, the female ring 12 is slightly rotated in the clockwise direction from the closed state of the cylindrical section 13a of the rubber-like member 13, so that the engaged state between the engage-groove 11A of the male ring 11 and the engage-groove 12A of the female ring 12 is released. Due to the resilient force of the rubber-like member 13, the female ring 12 is rotated at 180° in the counter clockwise direction, and the cylindrical section

13a is opened. For using a clamp or the like, the surgeon inserts it into the abdominal cavity through the opened cylindrical section 13a and the cylindrical member 111.

[0029] According to the valved trocar jacket tube in the first preferred embodiment, the outer diameter of the air container 112 can be changed by adjusting the air volume existing in the air container 112, so that the outer diameter of the cylindrical member 111 can be adjusted in accordance with the contour of the abdominal incision Pa. Since the cylindrical member 111 fits securely with the peritoneum P_3 due to its tension, leakage of an inert gas from the abdominal incision Pa can be prevented regardless of the contour of the abdominal incision Pa. Further, as described in the background of the invention, when a hand or a clamp or the like is inserted into the abdominal cavity through the valve 10, the rubber-like member 13 fits securely with the hand or the clamp or the like, so that leakage of an inert gas from the valved trocar jacket tube 100A can be suppressed to the minimum.

[0030] Fig. 6 shows a valved trocar jacket tube in the second preferred embodiment according to the invention, wherein a valved trocar jacket tube 100B comprises a tube 111A, which is formed by piling a lower end of a cylindrical member 111 of a skirt 110 inside to have a tube share, and further bonding or fusing it to a predetermined portion of the cylindrical member 111. The tube 111A comprises an air injecting tube 114 introduced on the upper portion of the valve 10 and a valve 115 provided at the pointed end of the air injecting tube 114. An air is injected into the tube 111A through the valve 115 and the air injecting tube 114.

[0031] According to the valved trocar jacket tube in the second preferred embodiment, the same effects as in the first preferred embodiment can be obtained. Further, since the skirt 110 is composed of only the cylindrical member 111, the number of necessary parts can be reduced, so that the manufacturing cost of the device can be reduced. In the second preferred embodiment, air-injecting menus can be provided in place of bonding or fusing the piled lower end of the cylindrical section 111.

[0032] Fig. 7 shows a valved trocar jacket tube in the third preferred embodiment according to the invention, wherein the valved trocar jacket tube 110C comprises upper and lower valves 10 placed opposite to each other, a connecting cylinder 120 for connecting the upper and lower valves 10, and a skirt 110 added to the lower valve which is similar to that in the first preferred embodiment. The upper end of the connecting cylinder 120 is bonded or fused in vicinity of the convex portion 13b which is fitted into the groove 11b of the male ring 11 contained in the upper valve 10, while the lower end of the connecting cylinder 120 is bonded or fused into the groove 12b of the female ring 12 contained in the lower valve 10. In the skirt 110, the upper end of the cylindrical member 111 is bonded or fused in vicinity of

the convex portion 13b fitted into the groove 11b of the male ring 11 contained in the lower valve 10 as in the first preferred embodiment. The connecting cylinder 120 and the skirt 110 may be detachable from one another for facilitating the substitution thereof.

[0033] According to the valved trocar jacket tube in the third preferred embodiment, the upper valve 10 is firstly opened so as to insert an instrument (s) or a hand therethrough, and the upper valve 10 is closed. Thereafter, the lower valve 10 is opened so as to insert the instrument(s) or a hand therethrough. In this case, even if the lower valve 10 is opened, since the gap defined by the inserted instrument(s) or hand is closed securely by the upper valve 10, leakage of the inert gas from the abdominal cavity as a result of application of pneumoperitoneum can be suppressed to the minimum.

[0034] Fig. 8A shows a valved trocar jacket tube in the fourth preferred embodiment according to the invention, wherein the valved trocar jacket tube 100D comprises a cylindrical member 111 composing a skirt 110, a circular ring-shaped elastic member 116 having an outer diameter of 100mm which is attached to a lower end of the cylindrical member 111, a ring-shaped air container 112 bonded or fused to an upper end of the cylindrical member 111.

[0035] Fig. 8B shows the valved trocar jacket tube 100D, as used in the fourth preferred embodiment. For mounting the valved trocar jacket tube 100D, the under side of the skirt 110 is inserted into an abdominal incision Pa of a patient P while forcing the ring-shaped elastic member 116 to have a slender, elliptical shape. Thereafter, the ring-shaped elastic member 116 is expanded into a circular configuration in an abdominal cavity to engage with the abdominal incision Pa as shown in Fig 8B. Thereafter, an air is injected into the air container 112 through the air injecting inlet 113 such that the air container is inflated to have desired contour and cross section respectively corresponding to the contour of the abdominal incision Pa and the total thickness of the skin P₁, the abdominal wall P₂, and the peritoneum P₃. At this time, since the skirt 110 is pulled and expanded by the air container 112, the cylindrical member 111 fits securely with the peritoneum P₃. When the female ring 12 is rotated at a predetermined angle, for example, 15° in either direction from the closed state of the cylindrical section 13a of the rubber-like member 13, the cylindrical section 13 is opened. For using the clamp or the like, the surgeon inserts the clamp or the like into the abdominal cavity through the opened cylindrical section 13a and the cylindrical member 111.

[0036] According to the valved trocar jacket tube 100D in the fourth preferred embodiment, the abdominal incision Pa can be securely held by injecting the air into the air container 112, so that the contact between the valved trocar jacket tube 100D and the skin P₁ can be improved. As a result, comparing to those in the first to third preferred embodiments, the valved trocar jacket tube 100D fits more securely with the abdominal inci-

sion Pa, so that the effect for preventing the leakage of the inert gas can be further improved. Further, since the volume of the air injected into the air container 112 can be changed in accordance with the contour of the abdominal incision Pa and the total thickness of the skin P₁, the abdominal wall P₂, and the peritoneum P₃, it is possible to apply the valved trocar jacket tube to more various patients and cases. Still further, since a space is provided around the air container 112 in the abdominal cavity, the surgeon can use this space to keep his hand beside, when the surgery is operated with inserting his hand into the abdominal cavity, so that it can facilitate the operation. In the fourth preferred embodiment, the air container 112 is secured to the skirt 110, however, it may be constructed to be detachable from the skirt 110.

[0037] Fig. 9 shows an air container 112, which is constructed to be detachable from the valved trocar jacket tube 100D in the fourth preferred embodiment, where in the air container 112 comprises a separated section 112A leading to a opening 112B. Herein, a cylindrical member 111 of a skirt 110 is inserted into the opening 112B through the separated section 112A and attached to an outer circumference of the cylindrical member 111 in practical use.

[0038] As a valved trocar jacket tube in the fifth preferred embodiment according to the invention, it is possible to provide a structure in which a valve 100 is added to an upper part of the valved trocar jacket tube 100D in the fourth preferred embodiment via a connecting cylinder 120 shown in Fig. 7.

[0039] As described above, in the valved trocar jacket tube according to the present invention, both ends of a first cylindrical elastic member are secured, one end of a second cylindrical elastic member is attached to one of first and second rings, which are so constructed that when they are rotated relatively in the opposite directions the opening of the first cylindrical elastic member is closed from the opening state, and a fluid container is provided at a predetermined position of the second cylindrical elastic member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid. According to this structure, it is possible to prevent leakage of an inert gas from an abdominal cavity without reducing the operativity during surgery.

Claims

1. A valved trocar jacket tube, comprising:

a first cylindrical elastic member having an opening with a predetermined sectional area; closing means including a first ring for securing one end of said first cylindrical elastic member and a second ring for securing another end of said first cylindrical elastic member, said first and second rings rotating relatively in the opposite directions respectively for closing said

opening from an opened state;

a second cylindrical elastic member, one end of which being attached to one of said first and second rings;

a ring member, which is elastically deformable and provided at another end of said second cylindrical elastic member; and

a fluid container provided at an upper part of an outer side of said second cylindrical elastic member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid;

wherein:

said first cylindrical elastic member is positioned outside an incised portion of a diseased part and functions as a valve;

said second cylindrical elastic member is positioned from outside to inside of said incised portion of said diseased part and maintains said incised portion at an opened state;

said ring member is positioned inside said incised portion of said diseased part and engaged with said incised portion of said diseased part; and

said fluid container is positioned outside said incised portion of said diseased part and fits securely said second cylindrical elastic member to side wells of said incised portion of said diseased part.

2. The valved trocar jacket tube, according to claim 1, wherein:

said fluid container is provided on said upper part or said outer side of said second cylindrical elastic member and detachable therefrom.

3. The valved trocar jacket tube, according to claim 1, wherein:

said closing means is connected to another closing means for closing an opening of a third cylindrical elastic member from an opened state.

4. A valved trocar jacket tube, comprises:

a first cylindrical elastic member having an opening with a predetermined sectional area; closing means including a first ring for securing one end of said first cylindrical elastic member and a second ring for securing another end of said first cylindrical elastic member, said first and second rings rotating relatively in the opposite directions respectively for closing said opening from an opened state;

a second cylindrical elastic member, one end of which being attached to one of said first and second rings; and

a fluid container provided at an upper part of an outer side of said second cylindrical elastic

member, which is inflated to have a ring shape by the increase of an inner pressure generated by injection of a fluid;

wherein:

said first cylindrical elastic member is positioned outside an incised portion of a diseased part and functions as a valve;

said second cylindrical elastic member is positioned from outside to inside of said incised portion of said diseased part and maintains said incised portion at an opened state; and said fluid container is positioned inside of said incised portion said diseased part and fits securely said second cylindrical elastic member to side walls of said incised portion of said diseased part.

5. The valved trocar jacket tube, according to claim 4, wherein:

said fluid container is bonded or fused to said another end of said second cylindrical elastic member.

6. The valved trocar jacket tube, according to claim 4, wherein:

said fluid container is constructed by piling a lower end of said second cylindrical elastic member to have a tube shape and bonding or fusing it to a predetermined portion of said second cylindrical elastic member.

7. The valved trocar jacket tube, according to claim 4, wherein:

said closing means is connected to another closing means for closing an opening of a third cylindrical elastic member from an opened state.

FIG. 1 PRIOR ART




FIG. 2 PRIOR ART




FIG. 3A




FIG. 3B




FIG. 4A





FIG. 4B



11b, 12b STEP PORTION
11 HALF RING
12 FEMALE RING
111 CYLINDRICAL MEMBER

13a CYLINDRICAL SECTION
11A, 12A ENGAGE-GROOVE
113 AIR INJECTION INLET

FIG. 5





FIG. 6



11 MALE RING
 12 FEMALE RING
 13 RUBBER MEMBER
 11A, 12A ENGAGE-GROOVE
 11b, 12b STEP PORTION

13b CONVEX PORTION
 13a CYLINDRICAL SECTION






FIG. 8A



11 MALE RING
12 FEMALE RING
13 RUBBER MEMBER
11a, 12a GROOVE
13b CONVEX PORTION
11b, 12b STEP PORTION
11A, 12A ENGAGE-GROOVE
13a CYLINDRICAL SECTION
111 CYLINDRICAL MEMBER
112 AIR CONTAINER

FIG. 8B



RING-SHAPED
RESILIENT
MEMBER


11 MALE RING
12 FEMALE RING
13 RUBBER MEMBER
11a, 12a GROOVE
13b CONVEX PORTION

11b, 12b STEP PORTION
11A, 12A ENGAGE-GROOVE
13a CYLINDRICAL SECTION
111 CYLINDRICAL MEMBER
112 AIR CONTAINER

Pa ABDOMINAL
INCISION

P SKIN
P2 ABDOMINALEUM
WALL
P3 PERITON

FIG. 9





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 8090

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 480 410 A (CUSCHIERI ALFRED ET AL) 2 January 1996 * column 3, line 16 - line 61 * * column 4, line 15 - line 18 *	1	A61B17/34
E	WO 98 48724 A (UNIVERSITY OF MASSACHUSETTS) 5 November 1998 * page 14, line 9 - page 15, line 27 * * page 21, line 11 - line 29; figures 2E, 5, 6 *	1-3	
A	US 5 522 791 A (LEYVA HORACIO A) 4 June 1996 * column 3, line 29 - line 36 * * column 5, line 8 - line 16 *	1, 4	
Y	WO 95 22289 A (BONADIO FRANK ; GAYA LTD (IE)) 24 August 1995 * page 14, line 19 - page 15, line 24; figure 5 *	4	
Y	WO 95 07056 A (BONADIO FRANK ; ENCORET LTD (IE)) 16 March 1995 * page 7, line 29 - page 8, line 11 * * page 9, line 27 - page 10, line 4; figures 7, 9 *	4	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 June 1999	Examiner Gérard, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 98 30 8090

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-06-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5480410 A	02-01-1996	AU 1997295 A	03-10-1995
		EP 0750472 A	02-01-1997
		WO 9524864 A	21-09-1995
WO 9848724 A	05-11-1998	US 5906577 A	25-05-1999
		AU 7274698 A	24-11-1998
US 5522791 A	04-06-1996	NONE	
WO 9522289 A	24-08-1995	IE 940150 A	04-10-1995
		IE 940613 A	04-10-1995
		IE 950055 A	07-08-1996
		AT 164303 T	15-04-1998
		AU 695770 B	20-08-1998
		AU 1717395 A	04-09-1995
		BR 9506817 A	09-09-1997
		CA 2183064 A	24-08-1995
		CN 1144471 A	05-03-1997
		CZ 9602404 A	16-04-1997
		DE 69501880 D	30-04-1998
		DE 69501880 T	23-07-1998
		EP 0744922 A	04-12-1996
		EP 0807416 A	19-11-1997
		ES 2115365 T	16-06-1998
		FI 963226 A	17-10-1996
		HU 76016 A	30-06-1997
		JP 9509079 T	16-09-1997
		NO 963421 A	14-10-1996
		NZ 279907 A	26-06-1998
WO 9507056 A	16-03-1995	PL 315939 A	09-12-1996
		US 5803921 A	08-09-1998
		ZA 9501378 A	24-10-1995
		AU 696289 B	03-09-1998
		AU 7507494 A	27-03-1995
		CA 2171177 A	16-03-1995
		EP 0776180 A	04-06-1997
		EP 0834279 A	08-04-1998
		EP 0888755 A	07-01-1999
		EP 0887047 A	30-12-1998
		EP 0887048 A	30-12-1998
		JP 9502624 T	18-03-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82